



TONE WINNER



Scan QR code

Guangzhou Tonewinner Electronics Co., Ltd

Tel.: 86-020-34797660/34796146

web: <http://www.tonewinner.com>

Alibaba web: <https://gztonewinner.en.alibaba.com/>

Address: NO.1, Hongsheng 3rd Road, Dashi Street,
Panyu District, Guangzhou, 511430, China

Speaker System User Manual



State High-tech enterprise



Dolby Certified Company



DTS Certified Company

I Instructions before use

This speaker system (here in after referred to as the speaker) has been strictly inspected and tested before leaving the factory, please do not disassemble it by yourself.

II Cleaning suggestion

Before cleaning, make sure the speaker is not in working state. When cleaning, please wipe gently with a soft cloth, do not use chemical solvents for cleaning.

III Install instruction

- ① Do not block the bass reflex ports.
- ② Avoid obstructions between the speaker and the listening position.
- ③ Do not place the speaker near heat sources (such as electric stoves, heaters, stoves) or other heating equipment (including amplifiers).
- ④ When the speaker is installed on the wall, the installation hole must be located on the cement pouring position or on the bricks load-bearing wall; the light brick wall, furred ceiling, calcium silicate board & etc shall not be directly drilled for installation of speakers.
- ⑤ Be sure to turn off the power amplifier before plug in /unplug the cable.
- ⑥ There should be no short circuit when the equipment is connected. After the connection is completed, please check again before use, otherwise it will easily cause damage to the speaker or power amplifier.
- ⑦ When connecting the speaker and the power amplifier, pay attention to the polarity , & make sure positive and negative poles are connected correctly, since the reverse connection will cause the poor sound quality and the inaccurate sound positioning.
- ⑧ When connecting the speakers and the power amplifier, please connect the corresponding speakers according to the markings on the rear panel of the power amplifier, and do not arbitrarily change or exchange positions, otherwise it may cause audio filed mess up, inaccurate sound positioning & poor sound quality.
- ⑨ The subwoofer signal line must be separated from strong electricity, and high-quality wire with shielding layer should be used to avoid signal attenuation or interference, resulting in reduced speaker volume and cause noise.

IV This speaker does not have waterproof and anti-corrosion functions. Do not place any liquid-filled objects on the speaker to prevent any liquid from entering the speaker, so as to avoid damage to the speaker or electric shock.

V The position of the plug, socket or electrical interface shall prevent the power cord, signal line from being entangled and being stepped on, so as to ensure the normal operation of the equipment.

VI Main Parameters

Please refer to the label on the speakers.

NOTE